CyberPower

RELAYIO500 LOCAL MANAGEMENT CARD

Offers users a solution for UPS status *monitoring* and local device control



CyberPower's RELAYIO500 is a local management solution that provides users the ability to monitor UPS status and events via 5 contact closure outputs. Easy to install in any compatible* CyberPower Smart App UPS with expansion slot.

Input contact closure allows the UPS to be shutdown remotely while on Battery Mode to preserver battery power in the event of a prolonged power outage.

A Three-Year Warranty ensures that this network management card has passed our highest quality standards in design, assembly, material and workmanship.

FEATURES

- Relay I/O Card for UPS status monitoring
- 5 relay output contact closures indicating UPS status info
- 1 relay input contact closure to shutdown UPS on Battery Mode
- Connections via DB9 port
- Hot-swappable (Plug-n-Play)

COMPATIBILITY

- OR Series UPS systems
- PR Series UPS systems
- OL1000RTXL2U, OL1500RTXL2U, OL2200RTXL2U. OL1500RTXL2UN, and OL3000RTXL2UHV

SPECIFICATIONS

| GENERAL | |
|----------------------------|-------------------------------------|
| Туре | Relay I/O UPS Monitoring Card |
| Contact Closure Outputs | 5 |
| Input Signal Contact | 1 - UPS shutdown in Battery Mode |
| Output Relay Rating (Max.) | 30VCD/125VAC, 3A (per relay) |
| External S/D Voltage | 7.5V to 12V |
| PHYSICAL | |
| Dimensions (WxHxD) (in.) | 1.65 x 0.6 x 3.2 |
| Dimensions (WxHxD) (mm.) | 41.8 x 14.2 x 81 |
| Weight (lbs.) | 0.11 |
| Weight (kg.) | 0.052 |
| SHIPPING DIMENSIONS | |
| Dimensions (WXHXD) (in.) | 6.6 x 2.3 x 6.4 |
| Dimensions (WxHxD) (mm.) | 168 x 58 x 162 |
| Weight (lbs.) | 0.35 |
| Weight (lbs.) | 0.16 |

| ENVIRONMENTAL | |
|---------------------------|---|
| Operating Temperature | 32°F to 104°F / 0°C to 40°C |
| Operating Humidity | 0% - 95% non-condensing |
| Operating Elevation | 0-10000 feet (0-3000 meters) |
| Storage Temperature | 14°F to 122°F / -10°C to 50°C |
| Storage Relative Humidity | 0% - 95% non condensing |
| Storage Elevation | 0-50000 feet (0-15000 meters) |
| COMPATIBILITY | |
| UPS Models | OR PR series and select OL series models, see compatibility chart for details |
| CERTIFICATIONS | |
| Environmental | RoHS compliant |
| WARRANTY | |
| Product Warranty | 3 years limited |
| Extended Warranty | WEXT5YR-ACC1A |