



## TS-h1090FU-7302P-128G

**CPU** AMD EPYC™ 7302P 16-core/32-thread processor, up to 3.3 GHz

**CPU Architecture** 64-bit x86

**Encryption Engine** Yes (AES-NI)

**System Memory** 128 GB RDIMM DDR4 ECC (8 x 16 GB)

**Maximum Memory** 1 TB+ (12 x 128 GB)

**Memory Slot** 12 x RDIMM DDR4

**Flash Memory** 5GB (Dual boot OS protection)

**Drive Bay** 10 x 2.5-inch U.2 PCIe NVMe / SATA 6Gbps

**Drive Compatibility** 2.5-inch U.2 NVMe Gen 4 x4 solid state drives  
2.5-inch SATA solid state drives

**Hot-swappable** Yes

**SSD Cache Acceleration Support** Yes

**SR-IOV** Yes

**2.5 Gigabit Ethernet Port (2.5G/1G/100M)** 2 (2.5G/1G/100M/10M)

**25 Gigabit Ethernet Port** 2 x 25GbE SFP28 SmartNIC port

**Wake on LAN (WOL)** Yes

**Jumbo Frame** Yes

**PCIe Slot** 2  
Slot 1: PCIe Gen4 x16  
Slot 2: PCIe Gen4 x16

**USB 3.2 Gen 1 port** 3

**Form Factor** Rackmount

**LED Indicators** Disk, Status, LAN, storage expansion port status

Buttons	Power, Reset
Dimensions (HxWxD)	44 × 430 × 580 mm
Weight (Net)	10.36 kg
Weight (Gross)	13.41 kg
Operating Temperature	0 - 40 °C (32°F - 104°F)
Storage Temperature	-20 - 70°C (-4°F - 158°F)
Relative Humidity	5-95% RH non-condensing, wet bulb: 27°C (80.6°F)
Power Supply Unit	550W PSU (x2), AC 100-240 V
Power Consumption: Operating Mode, Typical	157.97 W
Fan	5 x 60mm, 12VDC
System Warning	Buzzer
Max. Number of Concurrent Connections (CIFS) - with Max. Memory	10,000

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.