

Travel A/V Adapter: 3-in-1 USB-C to VGA, DVI or HDMI - 4K

Product ID: CDPVGDVHDB



This 3-in-1 travel adapter offers a portable solution for connecting your USB-C computer to a VGA, DVI, or HDMI® display.

The travel adapter is compatible with your DP alt mode computer. DP alt mode means your computer can pass a DisplayPort video signal through the USB-C port.

Stylish connectivity for your USB-C laptop

This travel adapter comes with a built-in black USB-C cable and works well with your Dell XPS™, MacBook and any device that supports USB-C DP alt mode.



All-in-one video connectivity, with travel in mind

Instead of carrying three separate video adapters in your laptop bag, this 3-in-1 adapter gives you all the video outputs you'll need. With VGA, DVI and HDMI outputs, this adapter lets you connect from your laptop's USB Type-C port to almost any boardroom or classroom display, without the inconvenience of carrying a separate adapter for each display type.

With support for multiple video outputs and a small-footprint design, this adapter is the ideal plug-and-play solution for travel or BYOD (Bring Your Own Device) applications around the office.

Innovative, built-in cable manager

The adapter features a built-in cable fastener. Simply tuck the cable into place along the side of the adapter for quick and secure storage while you're traveling to ensure the adapter is neatly stored in your travel bag.

Astonishing picture quality

The HDMI output on this travel adapter supports Ultra HD 4K resolutions, providing four times the picture quality of high-definition 1080p. The HDMI output is also backward compatible with lower resolutions, such as 1080p and 720p, so the adapter is also perfect for your legacy video equipment. The VGA and DVI outputs also support high-definition maximum resolutions of up to 1920 x 1200, so you can still enjoy excellent video quality.

The travel adapter is compatible with USB Type-C Intel® Thunderbolt™ 3 devices that are capable of outputting a DisplayPort signal.

The CDPVGDVHDB is backed by a StarTech.com 2-year warranty and free lifetime technical support.

Notes:

- macOS 10.12.6 or later is required for your MacBook to support this product.
- Your USB-C equipped host laptop must support video (DP alt mode) to work with this adapter. The adapter does not support USB Power Delivery.

Certifications, Reports and Compatibility



Applications

- Carry the adapter with you when you travel, and connect to almost any display
- Connect your BYOD Dell XPS, Chromebook Pixel, MacBook or other USB-C laptop or tablet to a provided VGA, DVI or HDMI display at work
- Connect a VGA, DVI or HDMI monitor to your USB-C laptop, to use as a secondary monitor

Features

- 3-in-1 adapter - USB-C to VGA, USB-C to DVI and USB-C to HDMI
- Maximum portability with built-in cable manager
- Astonishing picture quality with support for UHD 4K
- Plug-and-play installation
- Small footprint
- Lightweight design
- Compatible with USB Type-C Thunderbolt 3 devices that are capable of outputting a DisplayPort signal

Hardware	Warranty	2 Years
	Active or Passive Adapter	Active
	Adapter Style	Adapters
	AV Input	USB Type-C
	AV Output	DVI HDMI VGA
	Chipset ID	Cypress - CYPD2120-24LQXIT Cypress - CY7C65217 Analogix - ANX9847FN-AA-R MegaChips - MCDP2850-BC
Performance	Audio Specifications	HDMI output - 7.1 surround sound
	General Specifications	Only one video output is supported on the video adapter at a time. If multiple connections are made, only one of the outputs will function.
	Maximum Analog Resolutions	1920 x 1200 @ 60Hz
	Maximum Digital Resolutions	3840 x 2160 @ 30Hz
	Supported Resolutions	HDMI output: 3840 x 2160, 2560 x 1600, 1920 x 1200, 1920 x 1080, 1280 x 720 DVI and VGA output: 1920 x 1200, 1920 x 1080, 1280 x 720
	Video Revision	DisplayPort 1.2 HDMI 1.4
Wide Screen Supported	Yes	
Connector(s)	Connector A	1 - USB-C (24 pin) DisplayPort Alt Mode Male Input
	Connector B	1 - VGA (15 pin, High Density D-Sub) Female Output 1 - DVI-I (29 pin) Female Output 1 - HDMI (19 pin) Female Output
Special Notes / Requirements	Note	macOS 10.12.6 or later is required for your MacBook to support this product. Your USB-C equipped host laptop must support video (DP alt mode) to work with this adapter. The adapter does not support USB Power Delivery.
	System and Cable Requirements	Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter.
Environmental	Humidity	5~95% RH

	Operating Temperature	5°C to 35°C (41°F to 95°F)
	Storage Temperature	-40°C to 70°C (-40°F to 158°F)
Physical Characteristics	Cable Length	3.5 in [90 mm]
	Color	Black & Silver
	Enclosure Type	Plastic
	Product Height	0.7 in [18 mm]
	Product Length	4.3 in [110 mm]
	Product Weight	2.4 oz [67 g]
	Product Width	2.4 in [60 mm]
Packaging Information	Shipping (Package) Weight	0.4 lb [0.2 kg]
What's in the Box	Included in Package	1 - USB-C travel adapter

Product appearance and specifications are subject to change without notice.