HP E32k G5 4K USB-C Monitor



A Vision of Precision

Uniquely designed to deliver incredible visuals and extended flexibility, the HP E32k G5 4K USB-C Monitor redefines precision, so there's nothing between you and your best. Stylishly crafted with your comfort and the planet in mind, this 4K display is a powerhouse of productivity.



*Product image may differ from actual product

A View to Behold

• Whether you're focused in or looking at the bigger picture, you'll have sight of every detail you need to make things happen on this expansive, 31.5" diagonal 4K monitor¹. Take in every exquisite detail in an image or in a spreadsheet with four times the precision of a standard FHD monitor. And see it all in consistently vibrant colors through 99% sRGB color space.

Simple, Powerful Connections

• When you're working from home one day and the office the next, free yourself, your desk and your laptop from a mess of cables by simply connecting one USB-C[®] cable that connects your display and all your accessories—from webcam to keyboard—all while charging your laptop up to 65W. To make your workday even easier, instantly start up all your devices thanks to Single Power On² and secure a stable internet connection with RJ-45.

Comfort at Work

When doing your best relies on feeling your best, physical and viewing comfort is key. Easily find all-day
comfort with 4-way adjustability optimized by the step-by-step Ergonomic Setup Guide³. See comfortably
from day to night with the ambient light sensor that automatically adapts display brightness to fit your
surroundings, and enjoy added comfort with HP Eye Ease.

Inspiration on Display

Spark joy on your desk and in the world with a monitor built around you. The elegant design, including
integrated 3W dual speakers, elevates your office while maximizing space. Beyond the looks, be inspired by
a monitor that contains recycled plastics⁴ and metals⁵. And customize your space to boost your productivity
with the matching accessory ecosystem⁶.

Featuring

Ergonomic Setup Guide

Achieve all-day comfort when you apply the best practices from the Ergonomic Setup Guide.³

HP Eye Ease

HP Eye Ease is an always-on, low-blue light filter that helps keep your eyes comfortable throughout the day by reducing blue light without impacting color accuracy or adding a yellow color shift.⁷

Ambient Light Sensor

Automatically adjusts your screen's brightness to the lighting of your environment for comfortable viewing.

4K Resolution

Get lost in the captivating definition and ultra-precise details of 4K resolution. The pixel dense 3840 x 2160 resolution expands your workspace and transforms all your content into a remarkable, lifelike experience.¹

IPS Panel

No matter where you stand, IPS technology ensures image accuracy and consistency across wide 178-degrees horizontal and vertical viewing angles.

99% sRGB Color Space

Ideal color reproduction with minimal effort.⁷

Endless Adjustability

4-way adjustability for the perfect viewing angle.

More Ports. More Flexibility.

More ports means more capabilities. With an HDMI, DisplayPort[™], USB-C[®] plus 3 additional USB ports and 1 downstream 15W USB-C[®], you can connect or charge multiple devices like a headset and webcam.⁸

HP Display Manager

HP Display Manager makes remote management of the monitor easy. Simplify deployment, asset tracking, and remotely control monitor settings, like turning the power off.⁹

HP Display Center

Customize your display with easy, intuitive HP Display Center software.¹⁰

USB-C[®] Connectivity

Keep your set up simple and seamless with a display that has everything built in. Connect a keyboard and mouse to the ports on the back of this monitor and only one USB-C[®] cable to your notebook for data, video, and up to 65W of charging.

Dependable Internet Connectivity

Keep your set up simple and seamless with a display that has everything built in. Connect a keyboard and mouse to the ports on the back of this monitor and only one USB-C[®] cable to your notebook for data, video, and up to 65W of charging.⁹

Single Power On

Instantly turn on your display and PC, even when the lid is closed, by pressing the power button on the bottom of the display.²

Effortless Joypad OSD Button

It's never been easier to configure your display's settings right from the monitor. Simply navigate the on-screen menu with the joypad OSD button to adjust brightness, contrast, and color.

3-Sided Micro-Edge Bezel

See and do more on your screen with a 3-sided micro-edge bezel that maximizes your viewing area for a sleek design and virtually seamless dualmonitor setups.

Dual 3W Speakers

The integrated, side-firing 2x3W speakers deliver crystal-clear audio.

Materials that Matter

This monitor's enclosure consists of 90% recycled and renewable material.⁴

Mindful Metals

At HP, we don't stop when it comes to protecting our shared future. That's why this monitor was engineered to contain 25% recycled metals.¹⁵

Thoughtful Product Packaging

100% recyclable packaging that can stay out of landfills.^{11,12}

Increased Energy Efficiency

Reaching highest energy-saving standards with an ENERGY STAR® rating and EPEAT® Registration.^{13,14}

Matching Accessories

Customize your desk to fit your work needs with the matching accessory ecosystem.⁶

Boosted Manageability

With MAC address pass-through, PXE Boot, and Wake-on-LAN built in, easily manage your monitor fleet. Out-of-band manageability available with supported HP notebooks.^{16,17}

HP E32k G5 4K USB-C Monitor Specifications Table



	*Product image may differ from actual prod	
PARL data Series 21/26 15 dat 19/23 2.922 0° Dipuise Data P Construction 1000 1° Construction Non distribution of the set of one of the set o		
Name Add not Server and source and		
Consentation USES Severate definition Sete Scheming endering Notate Lob Sete Scheming endering Notate Lob Sete Scheming endering Sete Scheming endering Sete Scheming endering <td< td=""><td></td><td></td></td<>		
Severe sele Init Sile International Info Payota Calify Bits Freed. Mark And Lake and Like stand Severe selection Galaxies Like stand Severe selection Severe selection Severe selection Severe		
Appetite Definition Book head base and served on a served Spect ratio 160 ¹ Spect ratio 160 ¹ Spect ratio 160 ¹ Spect ratio 060 ¹ Spect ratio 010 ¹ Spect ratio 010 ¹ Spect ratio 010 ¹ Spect ratio 010 ¹		1000:11
Space Table Space Space Table Space<	Response ratio	5ms GtG (with overdrive) ¹
sine sexhap de la CPD Dielo 21007 / Bealadares seconted 600 e 480, 720 e 400, 200 e 700 e 400, 100 e 700, 1200 e 1020, 100 e 100, 200 e 1400, 100 e 210, 720 e 400 Bealadares seconted 600 e 400 e 700 e 400 e 100 e	Product color	Black head, black and silver stand
issuances sugarined 60x x 400, 720 x 400, 800 x 600, 100 x 720, 1200 x 1200, 1200 x 1000 x 1200, 1000 x 1200 x 12	Aspect ratio	
Biddle Matures On survey cannot be from ONL Ansignates, Hangle Ansignation, Hong	Native resolution	4K UHD (3840 × 2160) ^{1,2}
jake controls Management Information Exit Input, Soit: Input, Prese: Meau, Big Interast Verte and controls Use Input-Prese (Interput), It Sperification Interput), It Sperification Interput, It Sperification Interput, It Sperification Interput, It Sperification Interput Interp	Resolutions supported	640 x 480; 720 x 400; 800 x 600; 1024 x 768; 1280 x 720; 1280 x 1024; 1440 x 900; 1600 x 900; 1600 x 1200; 1680 x 1050; 1920 x 1080; 2560 x 1440; 3840 x 2160; 720 x 480
Number of Sig based induced bit Signification (Signification (Significati	Display features	On-screen controls; Single Power ON; Anti-glare; Height Adjust/Tilt/Swivel/Pivot; HP Eye Ease; Ambient light sensor
Note A 1000 ControlNote A 1000 Control (1000 Mapb). USB hyse-C* data: 1 SignS-Spect USB hyse-C* 5000s signaling rate Usb hor 15 W USB Hower BalaxyGRONo BipAloritar W Hower Sub 25%GraverDesting Information Sign 25%GraverDesting Infor	User controls	Management; Information; Exit; Input; Color; Image; Power; Menu; Brightness+
Camera No Hopade Camera Environmental Operating Transfactors 5 to 35°C System 100 - 240045 (Strict 5 to 35°C Waver 100 - 240045 (Strict 5 to 35°C Waver commention 2010 Ministraminal 2000 (Strict 5 to 35°C Waver commention 2010 Ministraminal 2000 (Strict 5 to 35°C Waver commention 2011 Ministraminal 2000 (Strict 5 to 35°C Waver commention 2011 Ministraminal 2000 (Strict 5 to 35°C Waver commention 2011 Ministraminal 2000 (Strict 5 to 35°C Waver commention 2011 Ministraminal 2000 (Strict 5 to 35°C Waver commention 2011 Ministraminal 2000 (Strict 5 to 25°C Strict 5 to 25°C		
Intervented Operation of a service of a ser	HDCP	Yes, DisplayPort™, HDMI and USB Type-C®
instructionalOperating humadry. 2016 p668 FIBoyer01 - 260 w5C0 M64Parect consumption261 N M meanum. 39 W Myslokil, 0.5 W SkandbylDimension261 N Is 25 x 16.5 Bit humadry. Impige. 261 N x 25 x 15.5 Bit humadry. Impige. 261 N x	Camera	No integrated camera
Aver consumption 2010 (Instantional), 390 (Instantional), 20.0000, 20.0	Environmental	
Dimensions 28.11 x 1.85 x 16.58 in (without hings) 28.11 x 2.94 x 1.658 in (with hings) 71.4 x 4.7 x 42.12 cm (with hangs) (14 x 7.47 x 42.12 cm (with hings) (without stand) Weight 15.52 kg. 64 dg (with stand) Mysial scuttry (back-word) ¹¹ Scuttry (back-word)	Power	100 - 240 VAC 50/60 Hz
Height 18.52 b; 8.4 kg lockh stand Thypidal scars/features Scaruly lock-ready ^{1,1} Stababis TO Centified EPR 4* ogstered ¹ EDRSKY STAR ^{ap} cardified Centification and compliance Bits RSM CIE CECC CE CECP CEL (CLUAUS EAC ENERCY STAR ^{ap} CEL (SD 9.41-30.7) KC/ACL, Korsa MEE'S EI-standyly. Morosoft WIQL Centification: NOM, PSB, SEME, TOO Centified; TOO Centified; Sage: TWAS ULCSA's VCQ, WEE; ESC LEG USE; DAV, EUC VEE; ESC LEG USE; DAV, EUC V	Power consumption	210 W (maximum), 39 W (typical), 0.5 W (standby)
Physical security features Security lock-ready ^{1,4} Scabbes TO Certifies EPEAT* registered*, ENBRGY STAM* rectified Certification and compliance Bits SISSEN (EC. CCG. CCG. CCG. CCG. CCG. CCG. CCG. C	Dimensions	$28.11 \times 1.85 \times 16.58$ in (without hinge); $28.11 \times 2.94 \times 16.58$ in (with hinge); $71.4 \times 4.7 \times 42.12$ cm (without hinge); $71.4 \times 7.47 \times 42.12$ cm (with hinge) (without stand)
Ecababis TCO Certified, EPEAT [®] registered [®] , ENBRGY STAR [®] , ECC, SO 92,41-307, KC/KCC, Korea MEPS IE-standby), MICIC, Ertification, NON, PSB, SEPN, TO Certified ECO Certification and compliance Distribution of Complex PSE, SCIE, USE, VILVAN, EXE, SUERKY STAR [®] , FCC, SO 92,41-307, KC/KCC, Korea MEPS IE-standby), MICIC, Ertification, NON, PSB, SEPN, TO Certified ECO Certification and compliance Statistication and compliance Distribution of comparing and compliance of the SEP, CEL, CHUNA, EXE, SUERKY STAR [®] , FCC, SO 92,41-307, KC/KCC, Korea MEPS IE-standby), MICIC, Ertification, NON, PSB, SEPN, TO Certification, Markins in the box Markins in the box Monitor, Warranty care, Dusk Setup. Poster, 1 USB Type -C to Type -C cable; AC power card ¹⁰ Markins in the box Monitor, Warranty care, Dusk Setup. Poster, 1 USB Type -C to Type -C cable; AC power card ¹⁰ Marking angle 140 pd Parel Bit depth 10 bit 18 bit + FRC) Marking angle 178* Marking angle 178* Marking angle 190* Marking 190 mm State biodentes 190 Marking 190 mm <	Weight	18.52 lb; 8.4 kg (with stand)
Careficiation and compaies Biss BMR LG CCCC ECE CECP. CEL CTUVUSE EAC, SHRERY STAPP, FCC, ISO 9241-907, KCACC, Korea MEPS IE-standby), Morsoft WHQL Certified Edge, TUVS, ULCIS, KCD, WEEE SCC, ISE, ME, TGA (Ubaine certificates, NGC SPE (Usane 2E Sistanable impact specifications Outside box and compaied cultarius and TOVIS sustanably scured and recycluble; Contains crean-bound recyclud plastic; 75% ITE-derived dioaed loop plastic, Aleast 25% recyclud media/A.S. Whits he box Montor, Warrenty, curcl. Divise Sustanably scured and recycluble; Contains crean-bound recyclud plastic; 75% ITE-derived dioaed loop plastic, Aleast 25% recyclud media/A.S. Whats he box Montor, Warrenty, curcl. Divise Sustanably scured and recycluble; Contains crean-bound recyclud plastic; 75% ITE-derived dioaed loop plastic, Aleast 25% recyclud media/A.S. Warranty 3 yaas Initied warranty Variaty 3 yaas Initied warranty Variaty 100 pla Variaty 102 Variaty 102 Variaty 102 Variaty 105 Variaty 103 Variaty	Physical security features	Security lock-ready ¹¹
Attinuition of Carifiel Edge, TUVS, CUL, VEER, ICE, URE, TMA, Unane certificates, NECS, Durane Ed statinable impact specifications Outfiel begar, TUVS, CUL, VEER, ICE, URE, TMA, Unane certificates, NECS, Durane Ed statinable impact specifications Outfiel begar, TUVS, CUL, VEER, ICE, URE, TMA, Unane certificates, NECS, Durane Ed statinable impact specifications Outfiel begar, TUVS, CUL, VEER, ICE, URE, TMA, Unane certificates, NECS, Durane Ed statinable impact specifications Outfiel begar, TUVS, SUL, ICEA, VECA, WEER, ICE, URE, TMA, Unane certificates, NECS, Durane Ed statinable impact specifications Outfiel begar, TUVS, SUL, ICEA, VECA, WEER, ICE, URE, TMA, Unane certificates, NECS, Durane Ed statinable impact specifications Monter, Warranty care, Outfiel begar, PER, Cul, PER, PER, PER, Cul, PER, PER, PER, PER, PER, PER, PER, PER	Ecolabels	TCO Certified; EPEAT® registered ⁴ ; ENERGY STAR® certified
Netaliant in pack 59.01.0000 Intel ⁴ 5.8.9 Marks in heb box Montor, Warranty, card, Quick Setup Poster, 1 USB Type-C° to Type-C cable; AC power cord ¹⁰ Warks in heb box A opi Panels bit dopi 10.0 pi Panels bit dopi 178° Panels bit dopi 3-side bordentess Panels bit dopi	Certification and compliance	
Name Age Reading System initiation Reading for (fop) 100 pi Reading for (fop) 100 bit (6 bt + FRC) Rectand Weng angle 105 (8 bt + FRC) Rectand Weng angle 78* Rectand Weng angle 3-sided borderless Rectand Weng angle 100 mm Anderless Rectand Weng angle 100 mm Anderless Rectand Weng angle 100 mm Anderless Restand Statements 0-side for the Mark anderless for the Mark anderless Restand Statement Angless and tement Angless and tement Angless	Sustainable impact specifications	Outside box and corrugated cushions are 100% sustainably sourced and recyclable; Contains ocean-bound recycled plastic; 75% ITE-derived closed loop plastic; At least 25% recycled metal ^{5,6,7,8,9}
Pakes per inch (pp)140 pin4Pakes per inch (pp)10 bit (B bit + FRC)Panel bit depth10 bit (B bit + FRC)Vertical Weng angle178*Horizontal Weng angle178*Saved Dodderless	What's in the box	Monitor; Warranty card; Quick Setup Poster; 1 USB Type-C $^{\circ}$ to Type-C cable; AC power cord 10
Panel bit depth10 bit 8 bit + FR()Vertical Viewing angle178°Vertical Viewing angle178°Vertical Viewing angle178°Vertical Viewing angle3-sided borderlessSeared3-sided borderlessViewel45%Viewel50°Viewel50°Pivot50°Pivot50°Viewel50°Viewel50°Viewel50°Viewel50°Viewel50°Viewel50°Viewel50°Viewel50°Viewel50°Viewel50°Viewel50°Viewel50°Viewel50°Viewel50°Viewel60°Vi	Warranty	3 years limited warranty
vertical viewing angle 178° Horizontal Viewing angle 178° Horizontal Viewing angle 178° Savel 3-sided borderiess Savel 3-sided borderiess Savel 245° Savel 245° Savel 245° Savel 245° View 90°	Pixels per inch (ppi)	140 ррі
Additional weight 178° Bazel 3-sided borderless Sided borderless 45° Sided borderless 45° Tilt -5 to +20° Vivot 90° Height adjustment range 150 mn Schonnunting 100 mm x 100 mm Hardness 3H Sicken free Yes Sicken free Yes Sicken free Yes Sing frequency (vertical) 30-6142 Display scan frequency (vertical) 30-6142 Display scan frequency (vertical) 30-6142 Display scan frequency (vertical) 30-135 KHz Display scan frequency (vertical) 30-135 KHz Display scan frequency (vertical) 99% sR68 Display color gamut 99% sR68 Display scan frequency (vertical) 99% sR68 Display scan frequency (vertical) 99% sR68 Display color gamut 99% sloped manger ¹² Vertical benchers HP Display Manager ¹² Through hung sloped vertical Vertical benchers HP Display Manager ¹² Through hung sloped vertical <td>Panel bit depth</td> <td>10 bit (8 bit + FRC)</td>	Panel bit depth	10 bit (8 bit + FRC)
Bazel3-side borderlessSivel:45°Tit:5 to *20°Vot:90°Height adjustment range:150 nm150 nm x 100 nm x 100 nmKardnensing:140 nm x 100 nmtardness:31Sizen treatment:41-glareSizen treatment:41-glareSizen treatment:41-glareSizen treatment:45-sizen (TV Low Blue Light Hardware Solution certified)Display scan frequency (whork):0-6-1/2Sizen frequency (whork):0-6-1/2Sizen frequency (hork):0-6-1/2Sizen frequency (hork):0-6-1/2 <t< td=""><td>/ertical viewing angle</td><td>178°</td></t<>	/ertical viewing angle	178°
Swlel:45°File:5 to 20°Pivot:90°Height adjustment range:50 mmU00 mm x 100 mm:00 mm x 100 mmKESA mounting:00 mm x 100 mmBardenson:3HScreen treatment:Anti-glareVers Leve State Sta	Horizontal viewing angle	178°
Title -5 to + 20° Pivot :90° Pivot :50 mm Height adjustment range :50 mm VESA mounting :00 mm x 100 mm VESA mounting :00 mm x 100 mm Factor :31 Screen treatment :34 Optimum :30 mm Ves :30 mm Piker-free :50 mm Objek scan frequency (vertical) :30 - 60 Hz Objek scan frequency (vertical) :30 - 60 Hz Objek scan frequency (vertical) :30 - 135 KHz Objek scan frequency (vortical) :0.135 KHz Objek scan frequency (vortical) :0.136 VIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII	Bezel	3-sided borderless
Physical±90°Height adjustment range150 nmVESA mounting000 mm x 100 mmHardness3HScreen treatmentAnti-giareFlicker-FreeYesLow blue light modesYes, HP Eye Ease (TÜV Low Blue Light Hardware Solution certified)Display scan frequency (Vertical)30-60 HzDisplay scan frequency (Vertical)30-50 HzDisplay scan frequency (Norizontal)30-50 HzDisplay color gamut50% sRGBDisplay color gamut2x 3 WManageent softwareHP Display Manager; In-Band MAC Address Pass Through (MAPT); Out-of-Band MAC Address Pass Through (MAPT); In-Band Wake on LAN (Wolc); Out-of-Band WAC Address Pass Through (MAPT); In-Band Wake on LAN (Wolc); Out-of-Band MAC Address Pass Through (MAPT); In-Band Wake on LAN (Wolc); Out-of-Band MAC Address Pass Through (MAPT); In-Band Wake on LAN (Wolc); Out-of-Band MAC Address Pass Through (MAPT); In-Band Wake on LAN (Wolc); Out-of-Band MAC Address Pass Through (MAPT); In-Band Wake on LAN (Wolc); Out-of-Band MAC Address Pass Through (MAPT); In-Band Wake on LAN (Wolc); Out-of-Band MAC Address P	Swivel	±45°
Height adjustment range150 mmVESA mounting100 mm x 100 mmHardness3HCarcent reatmentAnti-glareTicker-freeYesLow bulk light modesYes, HP Exes (TÜV Low Bluk Light Hardware Solution certified)Display scan frequency (vertical)30-60 HzDisplay scan frequency (vertical)30-155 KHzDisplay scan frequency (vertical)30-155 KHzDisplay scan frequency (vertical)10.135 KHzDisplay scan frequency (vertical)30-155 KHzDisplay scan frequency (vertical)30-155 KHzDisplay scan frequency (vertical)10.135 KHzDisplay scan frequency (vertical)30-155 KHzSplay scan frequency (vertical)30-155 KHzDisplay scan frequency (vertical)10.107 billion colors supported ³ Display scan frequency (vertical)10.107 billion colors supported ³ Display color gamut99% SRGESpeaker output power2 x3 WRemote manageabilityHD Display Center; HD Display Manager; In-Band MAC Address Pass Through (MAPT); Dut-of-Band MAC Address Pass Through (MAPT); In-Band Wake on LAN (Wol); Out-of-Band Wake on LAN (Wol); Sub-of-Band Wake on LAN (Wol); In-Band Wake on LAN (Wol); Sub-of-Band Wake on LAN	Tilt	-5 to +20°
KEA mounting100 mm x 100 mmHardnessHScreen treatmentAnti-glareFicker-freeVesLow blue light modesVes, HP Eyease(TÚV Low Blue Light Hardware Solution certified)Display scan frequery (vertical)30-60 HzDisplay scan frequery (vertical)30-60 HzDisplay scan frequery (vertical)30-135 KHzPote Joint Schu101 schuDisplay scan frequery (vertical)101 schuDisplay schu101 schuDisplay schu101 schuDisplay schu101 schuDisplay schu101 schuSchu101 schu <td>Pivot</td> <td>±90°</td>	Pivot	±90°
Hadness 3H Screen treatment Anti-glare Flicker-free Ves Low blue light modes Ves, HP Eye Ease (TÜV Low Blue Light Hardware Solution certified) Display scan frequercy (vertical) 30-60 Hz Display scan frequercy (vertical) 30-135 KHz Display scan frequercy (vertical) 30-135 KHz Display scan frequercy (vertical) 0.18 x 0.18 mm Display colors Up to 1.07 billion colors supported ³ Display colors Up to 1.07 billion colors supported ³ Display colors 99% sRGB Speaker output power 2 x 3 W Management software HP Display Manager ¹² Remote manageability Through HP Display Manager; In-Band MAC Address Pass Through (MAPT); Out-of-Band MAC Address Pass Through (MAPT); In-Band Wake on LAN (WoL); Out-of-Band Wake on	Height adjustment range	150 mm
Screen treatmentAnti-glareFilcker-freeYesLow blue light modesYes, HP Eye Ease (TÜV Low Blue Light Hardware Solution certified)Display scan frequency (vertical)30-60 HzDisplay scan frequency (horizontal)30-135 KHzDisplay scan frequency (horizontal)0.18 x 0.18 mmDisplay colorsUp to 1.07 billion colors supported ³ Display color gamut99% sRGBSpeaker output power2 x 3 WManagement softwareHP Display Center; HP Display Manager ¹² Remote manageabilityYes, DisplayPort [™] , HDMI and USB Type-C [®]	/ESA mounting	100 mm x 100 mm
Ricker-free Yes Low blue light modes Yes, HP Eye Ease (TÜV Low Blue Light Hardware Solution certified) Display scan frequency (vertical) 30-60 Hz Display scan frequency (vertical) 30-135 KHz Display scan frequency (vertical) 0-135 KHz Display scan frequency (vertical) 0.18 × 0.18 mm Display colors Up to 1.07 billion colors supported ³ Display color gamut 99% sRGB Speaker output power 2 x 3 W Management software HP Display Center; HP Display Manager ¹² Remote manageability Through HP Display Manager; In-Band MAC Address Pass Through (MAPT); Out-of-Band MAC Address Pass Through (MAPT); In-Band Wake on LAN (WoL); Out-of-Band Wake on LAN (WoL); PXE Boot ^{13,14} HDCP Yes, DisplayPort [™] , HDMI and USB Type-C [®]	Hardness	ЗН
wow blue light modes Yes, HP Eye Ease (TÜV Low Blue Light Hardware Solution certified) Display scan frequency (vertical) 30-60 Hz Display scan frequency (horizontal) 30-135 KHz Display scan frequency (horizontal) 0.18 x 0.18 mm Display colors Up to 1.07 billion colors supported ³ Display color gamut 9% sRGB Display color gamut 2 x 3 W Management software HP Display Center; HP Display Manager ¹² Remote manageability Through HP Display Manager; In-Band MAC Address Pass Through (MAPT); Out-of-Band MAC Address Pass Through (MAPT); In-Band Wake on LAN (WoL); Out-of-Band Wake on LAN (WoL); HDCP Yes, DisplayPort [™] , HDMI and USB Type-C [®]	Screen treatment	Anti-glare
Display scan frequency (vertical) 30-60 Hz Display scan frequency (horizontal) 30-135 KHz Display colors Up to 1.07 billion colors supported ³ Display color gamut 99% sRGB Speaker output power 2 x 3 W Management software HP Display Center; HP Display Manager ¹² Remote manageability Through HP Display Manager; In-Band MAC Address Pass Through (MAPT); Out-of-Band MAC Address Pass Through (MAPT); In-Band Wake on LAN (WoL); Out-of-Band Wake on LAN (WoL); PXE Boot ^{13,14} HDCP Yes, DisplayPort ^M , HDMI and USB Type-C [®]	Flicker-free	Yes
Display scan frequency (horizontal) 30-135 KHz Display scan frequency (horizontal) 30-135 KHz O 18 × 0.18 mm 0.18 × 0.18 mm Display colors Up to 1.07 billion colors supported ³ Display color gamut 99% sRGB Speaker output power 2 × 3 W Management software HP Display Center; HP Display Manager ¹² Remote manageability Through HP Display Manager; In-Band MAC Address Pass Through (MAPT); Out-of-Band MAC Address Pass Through (MAPT); In-Band Wake on LAN (WoL); Out-of-Band Wake on LAN (WoL); PXE Boot ^{13,14} HDCP Yes, DisplayPort ^M , HDMI and USB Type-C [®]	.ow blue light modes	Yes, HP Eye Ease (TÜV Low Blue Light Hardware Solution certified)
Display colors 0.18 x 0.18 mm Display colors Up to 1.07 billion colors supported ³ Display color gamut 99% sRGB Speaker output power 2 x 3 W Management software HP Display Center; HP Display Manager ¹² Remote manageability Through HP Display Manager; In-Band MAC Address Pass Through (MAPT); Out-of-Band MAC Address Pass Through (MAPT); In-Band Wake on LAN (WoL); Out-of-Band Wake on LAN (WoL); PXE Boot ^{13,14} HDCP Yes, DisplayPort ^M , HDMI and USB Type-C [®]	Display scan frequency (vertical)	30-60 Hz
Display colors Up to 1.07 billion colors supported ³ Display color gamut 99% sRGB Speaker output power 2 x 3 W Management software HP Display Center; HP Display Manager ¹² Remote manageability Through HP Display Manager; In-Band MAC Address Pass Through (MAPT); Out-of-Band MAC Address Pass Through (MAPT); In-Band Wake on LAN (WoL); Out-of-Band Wake on LAN (WoL); PXE Boot ^{13,14} HDCP Yes, DisplayPort ^M , HDMI and USB Type-C [®]	Display scan frequency (horizontal)	30-135 KHz
Display color gamut 99% sRGB Speaker output power 2 x 3 W Management software HP Display Center; HP Display Manager ¹² Remote manageability Through HP Display Manager; In-Band MAC Address Pass Through (MAPT); Out-of-Band MAC Address Pass Through (MAPT); In-Band Wake on LAN (WoL); Out-of-Band Wake on LAN (WoL); HDCP Yes, DisplayPort™, HDMI and USB Type-C®	Pixel pitch	0.18 x 0.18 mm
Speaker output power 2 x 3 W Management software HP Display Center; HP Display Manager ¹² Remote manageability Through HP Display Manager; In-Band MAC Address Pass Through (MAPT); Out-of-Band MAC Address Pass Through (MAPT); In-Band Wake on LAN (WoL); Out-of-Band Wake on LAN (WoL); HDCP Yes, DisplayPort [™] , HDMI and USB Type-C [®]	Display colors	Up to 1.07 billion colors supported ³
Management software HP Display Center; HP Display Manager ¹² Remote manageability Through HP Display Manager; In-Band MAC Address Pass Through (MAPT); Out-of-Band MAC Address Pass Through (MAPT); In-Band Wake on LAN (WoL); Out-of-Band Wake on LAN (WoL); MDCP Yes, DisplayPort™, HDMI and USB Type-C®	Display color gamut	99% sRGB
Management software HP Display Center; HP Display Manager ¹² Remote manageability Through HP Display Manager; In-Band MAC Address Pass Through (MAPT); Out-of-Band MAC Address Pass Through (MAPT); In-Band Wake on LAN (WoL); Out-of-Band Wake on LAN (WoL); MDCP Yes, DisplayPort™, HDMI and USB Type-C®	Speaker output power	2x3W
HDCP Yes, DisplayPort™, HDMI and USB Type-C®	Management software	HP Display Center; HP Display Manager ¹²
	Remote manageability	Through HP Display Manager; In-Band MAC Address Pass Through (MAPT); Out-of-Band MAC Address Pass Through (MAPT); In-Band Wake on LAN (WoL); Out-of-Band Wake on LAN (WoL); PXE Boot ^{13,14}
	HDCP	
	Ethernet	

HP E32k G5 4K USB-C Monitor

Messaging Footnotes

¹ 4K content required to view in 4K resolution

³ Ergonomic Setup Guide is available through HP Display Center. Host PC requires Windows 10 or higher. HP Display Center is available on the Microsoft store.

⁴ Recycled/Renewable materials made up of 85% ITE, 4.5% Ocean Bound Plastics, and 0.5% coffee grounds. Recycled plastic content percentage is based on the definition set in the IEEE 1680.1–2018 EPEAT® standard. HP defines renewable according to the Global Reporting Initiative Sustainability Reporting Standards. ⁵ Consists of 25% recycled metals. Recycled metal is expressed as a percentage of the total weight of the metal according to ISO 14021 definitions for metal parts over 25 grams.

⁶ Extended ecosystem sold separately.

Pall performance specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary, either higher or lower. ⁸ AC Power cable and USB-C® 3.1 cable included. All other cables sold separately.

 ⁹ HP Display Manager software agent must be running on a web server and host PC. Some limitations may apply to legacy monitors.
 ¹⁰ Host PC requires Windows 10 or higher. HP Display Center is available on the Microsoft store.
 ¹¹ 100% outer box/corrugate cushion packaging made from sustainably sourced certified and recycled fibers. Fiber cushions made from 100% recycled wood fiber and organic material. Any plastic cushions are made from >90% recycled plastic. Excludes plastic bags ¹⁴ Toolw outer box, or ugate custor packaging make profile sustainability sourced certified and recycled holes. File Fusions made from Youw recomplications.
 ¹² Recycling facilities not available in all locations.
 ¹³ HP Sustainability Report 2020 and HP Displays Sustainability Story 2021.
 ¹⁴ Based on US EPEAT® registration according to IEEE 1680.1-2020 EPEAT®. Status varies by country. Visit www.epeat.net for more information.
 ¹⁵ Recycled metal is expressed as a percentage of the total weight of the metal according to ISO 14021 definitions for metal parts over 25 grams.
 ¹⁶ Not all notebooks support remote manageability.
 ¹⁷ Out-of-band manageability only available with HP G7, G8 and G9 HP notebooks and not supported on non-HP devices.

Technical Specifications Footnotes

¹ All specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower

² DisplayPort[®] 1.4 or HDML 2) required to drive panel at its native resolution. The video card of the connected PC must be capable of supporting 3840 x 2160 at 60 Hz with 10-bit color using one DisplayPort[®], HDML The video card of the connected PC must be capable of supporting 3840 x 2160 at 60 Hz with 10-bit color using one DisplayPort[®], HDML The video card of the connected PC must be capable of supporting 3840 x 2160 at 60 Hz with 10-bit color using one DisplayPort[®], HDML The video card of the connected PC must be capable of supporting 3840 x 2160 at 60 Hz with 10-bit color using one DisplayPort[®], HDML The video card of the connected PC must be capable of supporting 3840 x 2160 at 60 Hz with 10-bit color using one DisplayPort[®], HDML The video card of the connected PC must be capable of supporting 3840 x 2160 at 60 Hz with 10-bit color using one DisplayPort[®], HDML The video card of the connected PC must be capable of supporting 3840 x 2160 at 60 Hz with 10-bit color using one DisplayPort[®], HDML The video card of the connected PC must be capable of supporting 3840 x 2160 at 60 Hz with 10-bit color using one DisplayPort[®], HDML The video card of the connected PC must be capable of supporting 3840 x 2160 at 60 Hz with 10-bit color using one DisplayPort[®], HDML The video card of the connected PC must be capable of supporting 3840 x 2160 at 60 Hz with 10-bit color using one DisplayPort[®], HDML The video card of the connected PC must be capable of supporting 3840 x 2160 at 60 Hz with 10-bit color using one DisplayPort[®], HDML The video card of the connected PC must be capable of support to the connected PC must be capable of support to the connected PC must be capable of support[®], HDML The video card of the connected PC must be capable of support[®], HDML The video card of the connected PC must be capable of support[®], HDML The video card of the connected PC must be capable of support[®], HDML The video card of the connected PC must be capable of support[®], HDML The video card of the connec

³ Number of colors through A-FRC technology. ⁴ EPEAT® registered where applicable. EPEAT® registration varies by country. See www.epeat.net for registration status by country. Based on US EPEAT® registration according to IEEE 1680.1-2018 EPEAT®. Status varies by country. Visit www.epeat.net for more information.

⁵ External power supplies. WWAN modules, power cords, cables, and peripherals excluded. Service parts obtained after purchase may not be Low Halogen.

⁶ ITE Derived Closed Loop Plastic percentage is based on the definition set in the IEEE 1680.1-2018 standard.
⁷ All plastic parts contain ocean-bound plastic. Percentage of ocean-bound plastic contained in each component varies by product.

⁸ Recycled metal is expressed as a percentage of the total weight of the metal according to ISO 14021 definitions for metal parts over 25 grams

⁹ 100% outer box packaging and corrugated cushions made from sustainably sourced certified and recycled fibers.
¹⁰ Included cables may vary by country.

¹ Lock sold separately.

LOCK SOU Separately.
 12 Host PC requires Windows 10 and above. HP Display Center is available on the Microsoft store.
 13 Not all notebooks support remote manageability.
 14 Out-of-band manageability only available with HP G7, G8 and G9 HP notebooks and not supported on non-HP devices.

Sign up for updates hp.com/go/getupdated

© Copyright 2023 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

DisplayPortTM is a trademark owned by the Video Electronics Standards Association (VESA®) in the United States and other countries. USB Type-C® and USB-C® are registered trademarks of USB Implementers Forum. ENERGY STAR® is a registered mark owned by the U.S. government September 2023