

Data Sheet

FUJITSU Server PRIMERGY RX2530 M4 Dual socket 1U rack server

Maximum productivity in a 1U housing

FUJITSU Server PRIMERGY will give you the servers you need to power any workload and changing business requirements. As business processes expand so does the need for applications. Each has its own resource footprint, so you need a way to optimize your computing to better serve your users. PRIMERGY systems will help you match your computing capabilities to your business priorities with our complete portfolio of expandable PRIMERGY tower servers for remote and branch offices, versatile rack-mount servers, compact and scalable blade systems, as well as hyper-converged scale-out servers. They convince by business proven quality with a wide range of innovations, highest efficiency cutting operational cost and complexity, provide more agility in daily operations, and integrate seamlessly to let help you concentrate on core business functions.

FUJITSU Server PRIMERGY RX rack systems are versatile rack-optimized servers providing best-in-class performance and energy efficiency, and thus form the "standard" in each data center. PRIMERGY RX servers deliver more than 20 years of development and production know-how resulting in extremely low failure rates below market average, and lead to continuous operations and outstanding hardware availability.

PRIMERGY RX2530 M4

The FUJITSU Server PRIMERGY RX2530 M4 is a rack server that provides high performance, expandability and energy efficiency in a 1U space saving housing. The PRIMERGY RX2530 M4 is ideal for virtualization, scale-out scenarios, and small databases as well as for high performance computing thanks to the high performance of the new Intel® Xeon® Processor Scalable Family CPUs with up to 28 cores and the latest DDR4 memory technology. Moreover, the RX2530 M4 delivers a great expandability by supporting up to 3,072 GB of main memory and is future-proof with M.2

device support and the latest iRMC S5 for server management of the next generation. NV-DIMMs will be supported from mid-2018 on. Up to 10 hard disk drives and optionally up to four high-speed PCIe SSDs offer a flexible storage configuration option. A variety of onboard DynamicLoM options, plus its dual-port embedded LAN meet future requirements, cost-optimized. The limited space of a 1U chassis offers highly efficient power supply units, their redundancy on demand and the optional Cool-safe® Advanced Thermal Design this will result in lower operational costs.



Features & Benefits

Main Features	Benefits
<p>Versatile Performance for any computing need</p> <ul style="list-style-type: none"> ■ Intel® Xeon® Processor Scalable Family CPUs with up to 28 cores relying on Intel® UltraPath Interconnect for an increased data rate between the CPUs ■ Up to 3,072 GB DDR4 memory with 2,666 MHz(24 DIMM slots), NV-DIMM coming mid-2018 ■ 4x PCIe Gen3 slots <p>Enhanced Features for enhanced Computing</p> <ul style="list-style-type: none"> ■ Onboard LAN 2x1 Gb/s for basic LAN and optional DynamicLoM with chipset 10Gb/s MAC ■ Mix&Match storage drive bays: Ideal scalability of either up to 8x 2.5-inch HDD/SSD + 1x ODD or up to 10x 2.5-inch, thereof optionally up to 4x PCIe 2.5-inch SSD SFF ■ 2x Internal M.2 device support for hypervisor installations ■ Power supply units with 96% energy efficiency ■ Fujitsu's Cool-safe® Advanced Thermal Design for higher ambient temperatures in the data center <p>Foundation for Trust and Security</p> <ul style="list-style-type: none"> ■ Fujitsu ServerView Suite including tools for installation and deployment, permanent status monitoring and control ■ BIOS, firmware and selected software are updated free of charge ■ TPM2.0 modules and latest operating system support <p>Simplified management</p> <ul style="list-style-type: none"> ■ iRMC S5 comes with new interactive web UI and conforms to Redfish providing unified API support for heterogeneous environment ■ RAID Controller embedded onboard 	<ul style="list-style-type: none"> ■ Ready for the future and data growth scenarios with the performance of two processors – marking the standard of tomorrow with an increase in computing power ■ DDR4 memories with higher bandwidth and lower consumption are the enabler; optimized for virtualization and clouds, data centers and high performance computing ■ Flexible expandability and diverse options for storage devices permits for the integration of existing and new SSD and HDD as needed. Less today, more in future – or vice versa. ■ The right Ethernet connection for all: Basic via onboard LAN, extended with DynamicLoM guarantees the highest flexibility to integrate the server into existing infrastructures – without overhauling the existing infrastructure ■ Flexible expandability and diverse options for storage devices permits for the integration of existing and new SSD and HDD as needed. Less today, more in future – or vice versa. ■ Not only “greener”, also less expensive over time: Highly efficient hot-plug power supplies save energy costs and make it easy to maintain the running system and ensure industry-leading uptime ■ Higher ambient temperatures lead to lower costs for cooling the data center ■ Lifecycle investment protection ■ The comprehensive tools of the Fujitsu ServerView Suite eases the administrators life ■ Hardware and Software driven security features are very important in a fast-paced world, especially considering cybercrime ■ Optimized for both: data centers and SMEs can now rely on latest generation iRMC S5 increasing security and server admin productivity ■ RAID support for the most common configurations is conveniently embedded on the system board and does not require a dedicated controller

Technical details

PRIMERGY RX2530 M4

Base unit	PRIMERGY RX2530 M4 LFF	PRIMERGY RX2530 M4 SFF	PRIMERGY RX2530 M4 SFF	PRIMERGY RX2530 M4 SFF
Housing types	Rack	Rack	Rack	Rack
Storage drive architecture	4x 3.5-inch SAS/SATA	4x 2.5-inch SAS/SATA	8x 2.5-inch SAS/SATA	10x 2.5-inch SAS/SATA/PCIe
Power supply	Hot-plug	Hot-plug	Hot-plug	Hot-plug
Product Type	Dual Socket Rack Server	Dual Socket Rack Server	Dual Socket Rack Server	Dual Socket Rack Server

Mainboard

Mainboard type	D3383
Chipset	Intel® C624
Processor quantity and type	1 - 2 x Intel® Xeon® Processor Scalable Family

Intel® Xeon® Bronze Processor	Intel® Xeon® Bronze 3104 processor (6C nHT, 1.70 GHz, TLC: 8.25 MB, Turbo: 1.70 GHz, 9.6 GT/s, Mem bus: 2,133 MHz, 85 W, AVX Base 1.30 GHz, AVX Turbo 1.30 GHz)
	Intel® Xeon® Bronze 3106 processor (8C nHT, 1.70 GHz, TLC: 11 MB, Turbo: 1.70 GHz, 9.6 GT/s, Mem bus: 2,133 MHz, 85 W, AVX Base 1.30 GHz, AVX Turbo 1.30 GHz)

Intel® Xeon® Silver Processor	Intel® Xeon® Silver 4108 processor (8C, 1.80 GHz, TLC: 11 MB, Turbo: 2.10 GHz, 9.6 GT/s, Mem bus: 2,400 MHz, 85 W, AVX Base 1.30 GHz, AVX Turbo 1.30 GHz)
	Intel® Xeon® Silver 4110 processor (8C, 2.10 GHz, TLC: 11 MB, Turbo: 2.40 GHz, 9.6 GT/s, Mem bus: 2,400 MHz, 85 W, AVX Base 1.70 GHz, AVX Turbo 2.10 GHz)
	Intel® Xeon® Silver 4112 processor (4C, 2.60 GHz, TLC: 8.25 MB, Turbo: 2.90 GHz, 9.6 GT/s, Mem bus: 2,400 MHz, 85 W, AVX Base 2.20 GHz, AVX Turbo 2.60 GHz)
	Intel® Xeon® Silver 4114 processor (10C, 2.20 GHz, TLC: 13.75 MB, Turbo: 2.50 GHz, 9.6 GT/s, Mem bus: 2,400 MHz, 85 W, AVX Base 1.80 GHz, AVX Turbo 2.20 GHz)
	Intel® Xeon® Silver 4116 processor (12C, 2.10 GHz, TLC: 16.5 MB, Turbo: 2.40 GHz, 9.6 GT/s, Mem bus: 2,400 MHz, 85 W, AVX Base 1.70 GHz, AVX Turbo 2.10 GHz)

Intel® Xeon® Gold Processor

Intel® Xeon® Gold 5115 processor (10C, 2.40 GHz, TLC: 13.75 MB, Turbo: 2.80 GHz, 10.4 GT/s, Mem bus: 2,400 MHz, 85 W, AVX Base 2.00 GHz, AVX Turbo 2.40 GHz)
Intel® Xeon® Gold 5118 processor (12C, 2.30 GHz, TLC: 16.5 MB, Turbo: 2.70 GHz, 10.4 GT/s, Mem bus: 2,400 MHz, 105 W, AVX Base 1.90 GHz, AVX Turbo 2.30 GHz)
Intel® Xeon® Gold 5120 processor (14C, 2.20 GHz, TLC: 19.25 MB, Turbo: 2.60 GHz, 10.4 GT/s, Mem bus: 2,400 MHz, 105 W, AVX Base 1.80 GHz, AVX Turbo 2.20 GHz)
Intel® Xeon® Gold 5122 processor (4C, 3.60 GHz, TLC: 16.5 MB, Turbo: 3.70 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 105 W, AVX Base 3.30 GHz, AVX Turbo 3.60 GHz)
Intel® Xeon® Gold 6126 processor (12C, 2.60 GHz, TLC: 19.25 MB, Turbo: 3.30 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 125 W, AVX Base 2.20 GHz, AVX Turbo 2.90 GHz)
Intel® Xeon® Gold 6128 processor (6C, 3.40 GHz, TLC: 19.25 MB, Turbo: 3.70 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 115 W, AVX Base 2.90 GHz, AVX Turbo 3.60 GHz)
Intel® Xeon® Gold 6130 processor (16C, 2.10 GHz, TLC: 22 MB, Turbo: 2.80 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 125 W, AVX Base 1.70 GHz, AVX Turbo 2.40 GHz)
Intel® Xeon® Gold 6132 processor (14C, 2.60 GHz, TLC: 19.25 MB, Turbo: 3.30 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 140 W, AVX Base 2.20 GHz, AVX Turbo 2.90 GHz)
Intel® Xeon® Gold 6134M processor (8C, 3.20 GHz, TLC: 24.75 MB, Turbo: 3.70 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 130 W, AVX Base 2.70 GHz, AVX Turbo 3.40 GHz)
Intel® Xeon® Gold 6134 processor (8C, 3.20 GHz, TLC: 24.75 MB, Turbo: 3.70 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 130 W, AVX Base 2.70 GHz, AVX Turbo 3.40 GHz)
Intel® Xeon® Gold 6136 processor (12C, 3.00 GHz, TLC: 24.75 MB, Turbo: 3.30 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 150 W, AVX Base 2.60 GHz, AVX Turbo 3.30 GHz)
Intel® Xeon® Gold 6138 processor (20C, 2.00 GHz, TLC: 27.5 MB, Turbo: 2.70 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 125 W, AVX Base 1.60 GHz, AVX Turbo 2.30 GHz)
Intel® Xeon® Gold 6140M processor (18C, 2.30 GHz, TLC: 24.75 MB, Turbo: 3.00 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 140 W, AVX Base 1.90 GHz, AVX Turbo 2.60 GHz)
Intel® Xeon® Gold 6140 processor (18C, 2.30 GHz, TLC: 24.75 MB, Turbo: 3.00 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 140 W, AVX Base 1.90 GHz, AVX Turbo 2.60 GHz)
Intel® Xeon® Gold 6142M processor (16C, 2.60 GHz, TLC: 22 MB, Turbo: 3.30 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 150 W, AVX Base 2.20 GHz, AVX Turbo 2.90 GHz)
Intel® Xeon® Gold 6142 processor (16C, 2.60 GHz, TLC: 22 MB, Turbo: 3.30 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 150 W, AVX Base 2.20 GHz, AVX Turbo 2.90 GHz)
Intel® Xeon® Gold 6144 processor (8C, 3.50 GHz, TLC: 24.75 MB, Turbo: 4.10 GHz, 10.4 GT/s, Mem bus: 2,666 MHz, 150 W, AVX Base 2.80 GHz, AVX Turbo 3.50 GHz)
Intel® Xeon® Gold 6146 processor (12C, 3.20 GHz, TLC: 24.75 MB, Turbo: 3.90 GHz, 10.4 GT/s, Mem bus: 2,666 MHz, 165 W, AVX Base 2.60 GHz, AVX Turbo 3.30 GHz)
Intel® Xeon® Gold 6148 processor (20C, 2.40 GHz, TLC: 27.5 MB, Turbo: 3.10 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 150 W, AVX Base 1.90 GHz, AVX Turbo 2.60 GHz)
Intel® Xeon® Gold 6150 processor (18C, 2.70 GHz, TLC: 24.75 MB, Turbo: 3.40 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 165 W, AVX Base 2.30 GHz, AVX Turbo 3.00 GHz)
Intel® Xeon® Gold 6152 processor (22C, 2.10 GHz, TLC: 30.25 MB, Turbo: 2.80 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 140 W, AVX Base 1.70 GHz, AVX Turbo 2.40 GHz)
Intel® Xeon® Gold 6154 processor (18C, 3.00 GHz, TLC: 24.75 MB, Turbo: 3.70 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 200 W, AVX Base 2.60 GHz, AVX Turbo 3.30 GHz)

Intel® Xeon® Platinum Processor	Intel® Xeon® Platinum 8153 processor (16C, 2.00 GHz, TLC: 22 MB, Turbo: 2.30 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 125 W, AVX Base 1.60 GHz, AVX Turbo 2.00 GHz)
	Intel® Xeon® Platinum 8160M processor (24C, 2.10 GHz, TLC: 33 MB, Turbo: 2.80 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 150 W, AVX Base 1.80 GHz, AVX Turbo 2.50 GHz)
	Intel® Xeon® Platinum 8160 processor (24C, 2.10 GHz, TLC: 33 MB, Turbo: 2.80 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 150 W, AVX Base 1.80 GHz, AVX Turbo 2.50 GHz)
	Intel® Xeon® Platinum 8164 processor (26C, 2.00 GHz, TLC: 35.75 MB, Turbo: 2.70 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 150 W, AVX Base 1.60 GHz, AVX Turbo 2.30 GHz)
	Intel® Xeon® Platinum 8168 processor (24C, 2.70 GHz, TLC: 33 MB, Turbo: 3.40 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 205 W, AVX Base 2.30 GHz, AVX Turbo 3.00 GHz)
	Intel® Xeon® Platinum 8170M processor (26C, 2.10 GHz, TLC: 35.75 MB, Turbo: 2.80 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 165 W, AVX Base 1.70 GHz, AVX Turbo 2.40 GHz)
	Intel® Xeon® Platinum 8170 processor (26C, 2.10 GHz, TLC: 35.75 MB, Turbo: 2.80 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 165 W, AVX Base 1.70 GHz, AVX Turbo 2.40 GHz)
	Intel® Xeon® Platinum 8176M processor (28C, 2.10 GHz, TLC: 38.5 MB, Turbo: 2.80 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 165 W, AVX Base 1.70 GHz, AVX Turbo 2.40 GHz)
	Intel® Xeon® Platinum 8176 processor (28C, 2.10 GHz, TLC: 38.5 MB, Turbo: 2.80 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 165 W, AVX Base 1.70 GHz, AVX Turbo 2.40 GHz)
	Intel® Xeon® Platinum 8180M processor (28C, 2.50 GHz, TLC: 38.5 MB, Turbo: 3.20 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 205 W, AVX Base 1.70 GHz, AVX Turbo 2.30 GHz)
	Intel® Xeon® Platinum 8180 processor (28C, 2.50 GHz, TLC: 38.5 MB, Turbo: 3.20 GHz, 10.4 GT/s, Mem bus: 2,667 MHz, 205 W, AVX Base 1.70 GHz, AVX Turbo 2.30 GHz)
Memory slots	24 (12 DIMMs per CPU, 6 channels with 2 slots per channel)
Memory slot type	DIMM (DDR4)
Memory capacity (min. - max.)	8 GB - 3.072 GB
Memory protection	Advanced ECC Memory Scrubbing SDDC Rank sparing memory support Memory Mirroring support
Memory notes	Memory Mirroring with identical modules in both channel pairs of a bank (6 modules per bank), Rank sparing or Performance Mode with identical modules in all six channels (6 modules per bank).
Memory options	8 GB (1 module(s) 8 GB) DDR4, registered, ECC, 2,666 MHz, PC4-2666, DIMM, 1Rx4 8 GB (1 module(s) 8 GB) DDR4, registered, ECC, 2,666 MHz, PC4-2666, DIMM, 2Rx8 16 GB (1 module(s) 16 GB) DDR4, registered, ECC, 2,666 MHz, PC4-2666, DIMM, 1Rx4 16 GB (1 module(s) 16 GB) DDR4, registered, ECC, 2,666 MHz, PC4-2666, DIMM, 2Rx4 16 GB (1 module(s) 16 GB) DDR4, registered, ECC, 2,666 MHz, PC4-2666, DIMM, 2Rx8 32 GB (1 module(s) 32 GB) DDR4, registered, ECC, 2,666 MHz, PC4-2666, DIMM, 2Rx4 64 GB (1 module(s) 64 GB) DDR4 3DS, registered, ECC, 2,666 MHz, PC4-2666, DIMM, 4Rx4 64 GB (1 module(s) 64 GB) DDR4, registered, ECC, 2,666 MHz, PC4-2666, LRDIMM, 4Rx4 128 GB (1 module(s) 128 GB) DDR4 3DS, registered, ECC, 2,666 MHz, PC4-2666, DIMM, 8Rx4
Interfaces	
USB 3.0 ports	5 x USB 3.0 (2x front, 2x rear, 1x internal) - for base unit with 10x 2.5" drives 1x USB 2.0 front only
Graphics (15-pin)	2 x VGA (thereof 1x front optional - not for base unit with 10x 2.5" drives)
Serial 1 (9-pin)	1 x optional (occupies PCIe slot)
Management LAN (RJ45)	1 x dedicated management LAN port for iRMC S5 (10/100/1000 Mbit/s) Management LAN traffic can be switched to shared onboard LAN controller port, speed and connector is related to installed interface card.
Onboard or integrated Controller	
RAID controller	All hardware storage controller options are described under Components
SATA Controller	Intel® C624, 1 x SATA channel for ODD

Onboard or integrated Controller				
LAN Controller	2 x 10 Gbit/s Ethernet (RJ45)#2 x 10 Gbit/s SFP+#2 x 1Gbit/s onboard#4 x 1 Gbit/s Ethernet (RJ45)#4 x 10 Gbit/s SFP+#All supported features are described in relevant system configurator. Wake-on-LAN supported on onboard Port 1 and 2. PXE-Boot via LAN from PXE server, iSCSI / FCoE boot (also diskless). Extra LAN controller(PCIe Cards) are listed below. (i210 LAN card via project release possible)#Intel® C624#Optional DynamicLoM OCP adaptors:			
Remote management controller	Integrated Remote Management Controller (iRMC S5, 1,024 MB attached memory incl. graphics controller) IPMI 2.0 compatible			
Onboard controller notes	Onboard 8x S-ATA 6Gbit/s RAID Controller (RAID 0,1) for up to 8x S-ATA drives available.			
Trusted Platform Module (TPM)	Infineon / TPM 1.2 or TPM 2.0 module; TCG compliant (option)			
Slots				
PCI-Express 3.0 x8	1 x Low profile (2nd processor required for slot 4)			
PCI-Express 3.0 x16	3 x Low profile (2nd processor required for slot 4); 1x16 if fh slot selected			
Slot Notes	Slot 1 (internal): PCIe Gen3 x8 @CPU1 is dedicated for the modular RAID Controller. Slot 2: PCIe Gen3 x16 @CPU1 for low profile cards with up to 167mm length Slot 3: PCIe Gen3 x16 @CPU1 for low profile cards with up to 167mm length Slot 4 standard: PCIe Gen3 x16 @CPU2 for low profile cards with up to 167mm length Slot 4 option: PCIe Gen3 x16 @CPU2 for full height cards with up to 167mm length (!in this case, slot 3 is not available)			
Drive bays (Base unit specific)				
Storage drive bays	up to 8 x 2.5-inch, 10 x 2.5-inch or 4 x 3.5-inch baseunit			
Accessible drive bays	1 x 5.25/0.4-inch for CD-RW/DVD			
Notes accessible drives	Not for 10 x 2.5-inch base unit. All possible options described in relevant system configurator.			
Drive bays (Base unit specific)				
Storage drive bays	up to 4x 3.5" (LFF) hot plug drives (SAS/SATA)	up to 4x 2.5" (SFF) hot plug drives (SAS/SATA); option for upgrade to 8x 2.5" (SFF) hot plug drives	up to 8x 2.5" (SFF) hot plug drives (SAS/SATA)	up to 10x 2.5" (SFF) hot plug drives (SAS/SATA); thereof up to 4x bays prepared for 2.5" PCIe SSD
Optional accessible drives	Ultra slim 9.5mm optical drive (optional)	Ultra slim 9.5mm optical drive (optional)	Ultra slim 9.5mm optical drive (optional)	n/a
General system information				
Number of fans	8			
Fan configuration	redundant / hot-plug			
Fan notes	3+1 fan modules for 1 CPU configuration; 7+1 fan modules for 2 CPU configuration			
Operating panel				
Operating buttons	On/off switch Reset button NMI button ID button			
Status LEDs	System status (orange / yellow) Identification (blue) Hard disks access (green) Power (amber / green) At system rear side: System status (orange / yellow) Identification (blue) LAN connection (green) LAN speed (green / yellow)			

BIOS

BIOS features	UEFI compliant Legacy BIOS compatibility customer configuration option Secure boot support ROM based setup utility GPT support for boot drives larger than 2.2 TB Memory Redundancy support (Mirroring, Sparing) IPMI support Recovery BIOS BIOS settings save and restore Local BIOS update from USB device Online update tools for main Linux versions Local and remote update via ServerView Update Manager IPv4/IPv6 remote PXE & iSCSI boot support
----------------------	--

Operating Systems and Virtualization Software

Certified or supported operating systems and virtualization software	Microsoft® Hyper-V Server 2016 Microsoft® Windows Server® 2016 Datacenter Microsoft® Windows Server® 2016 Standard Microsoft® Windows Server® 2016 Essentials Microsoft® Windows Storage Server 2016 Standard Microsoft® Hyper-V Server 2012 R2 Microsoft® Windows Server® 2012 R2 Datacenter Microsoft® Windows Server® 2012 R2 Standard Microsoft® Windows Server® 2012 R2 Essentials Microsoft® Windows Server® 2012 R2 Foundation Microsoft® Windows Storage Server 2012 R2 Standard VMware vSphere™ 6.5 VMware vSphere™ 6.0 SUSE® Linux Enterprise Server 12 SUSE® Linux Enterprise Server 11 Red Hat® Enterprise Linux 7 Red Hat® Enterprise Linux 6 Oracle® Linux 7
Operating system release link	http://docs.ts.fujitsu.com/dl.aspx?id=d4ebd846-aa0c-478b-8f58-4cfbf3230473
Operating system notes	Support of other Linux derivatives on demand

Server Management

Standard	<ul style="list-style-type: none"> ServerView Suite (Deploy) <ul style="list-style-type: none"> ServerView Installation Manager ServerView Scripting Toolkit ServerView Suite (Control) <ul style="list-style-type: none"> ServerView Operations Manager (incl. PDA and ASR & R) ServerView Agents and CIM provider ServerView Agentless Management ServerView System Monitor SVOM- Event Manager ServerView RAID Manager SVOM- Threshold Manager Power Monitor (monitoring the Power Consumption) Power Management (iRMC) Storage Management (server) with SVOM/SV-RAID ServerView Suite (Maintain) <ul style="list-style-type: none"> iRMC S5 (Remote Management) System Update Manager (BIOS, Firmware, Windows Drives and SV Agents) Performance management (SVOM) Asset Management Primecollect Customer Self Service Online Diagnostics ServerView Suite (Integrate) <ul style="list-style-type: none"> ServerView Integration packs for MS System Center, VMware vCenter, VMware vRealize, Nagios, and HP SIM
Option	<ul style="list-style-type: none"> ServerView Suite (Maintain) <ul style="list-style-type: none"> ServerView eLCM iRMC Advanced Pack incl. Advanced Video Redirection (AVR), video capturing and Virtual Media ServerView Suite (Dynamize) <ul style="list-style-type: none"> ServerView Virtual IO Manager (SVIOM) Resource Orchestrator- virtual edition Resource Orchestrator- Cloud edition
Server Management notes	Regarding dependencies for ServerView Suite software products see dedicated product data sheets.
Dimensions / Weight	
Rack (W x D x H)	483 mm (Bezel) / 435mm (Body) x 770.7 x 43 mm
Mounting Depth Rack	748.2 mm
Height Unit Rack	1 U
19" rackmount	Yes
Mounting Cable depth rack	200 mm (1,000 mm Rack recommended)
Weight	up to 16 kg
Weight notes	Actual weight may vary depending on configuration
Rack integration kit	Rack integration kit as option
Environment	
Operating ambient temperature	5 - 45 °C (41 - 113 °F)
Operating temperature note	Cool-safe® Advanced Thermal Design (above 35 °C or below 10 °C) depending on configuration. For detailed information see relevant system configurator.
Operating relative humidity	10 - 85 % (non condensing)
Operating environment	FTS 04230 – Guideline for Data Center (installation specification)
Operating environment link	http://docs.ts.fujitsu.com/dl.aspx?id=e4813edf-4a27-461a-8184-983092c12dbe
Noise emission	Measured according to ISO 7779 and declared according to ISO 9296
Sound pressure (LpAm)	Noise typical configuration: 24 dB(A) (idle) / 39 dB(A) (operating)
Sound power (LWAd; 1B = 10dB)	Noise minimum configuration: 4.1 B (idle) / 5.6 B (operating) Noise typical configuration: 5.4 B (idle) / 6.2 B (operating)
Noise notes	Noise emissions depends on operation modes, system configuration and ambient temperature. Typical hardware configuration which is the base for measurement according to ISO 7779: 2x PSU 450W. 2x CPU Xeon 85W, 4x RAM 16GB, 2x HDD 500GB SATA, 6x LAN 1 Gbit/s

Electrical values	
Power supply configuration	1 x hot-plug power supply or 2 x hot-plug power supply for redundancy
Hot-plug power supply redundancy	Optional
Active power (max. configuration)	883 W
Apparent power (max. configuration)	892 VA
Heat emission (max. configuration)	3178.8 kJ/h (3012.9 BTU/h)
Rated current max.	10.5 A (100 V) / 5.0 A (240 V)
Active power note	To estimate the power consumption of different configurations use the Power Calculator of the System Architect: http://configurator.ts.fujitsu.com/public/
Power supply	450W hot-plug, 94% (Platinum efficiency), 100-240V, 50 / 60Hz 800W hot-plug, 94% (Platinum efficiency), 100-240V, 50 / 60Hz 800W hot-plug, 96% (Titanium efficiency), 200-240V, 50 / 60Hz 1200W hot-plug, 94% (Platinum efficiency), 100-240V, 50 / 60Hz; 110V range: 1000W, less than 110V: 900W 800W hot-plug, 94% (Platinum efficiency) –48V DC voltage
Power supply notes	Power Safeguard adapts system performance in case the power requirements exceeds supply limits. 96% Titanium Power supply unit is only released for 200-240V
Compliance	
Global	CB RoHS (Substance limitations in accordance with global RoHS regulations) WEEE (Waste electrical and electronic equipment)
Germany	GS
Europe	CE
USA/Canada	CSAc/us FCC Class A ICES-003 / NMB-003 Class A
Japan	VCCI:V3 Class A + JIS 61000-3-2
Russia	EAC
South Korea	KC
China	CCC (planned)
Australia/New Zealand	RCM
Taiwan	BSMI (planned)
India	BIS R41004006
Compliance link	https://sp.ts.fujitsu.com/sites/certificates
Compliance notes	There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request. * Warning: This is a class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.

Components

Optical drives	Blu-ray Disc™ Triple Writer, (6x BD-RW, 8x DVD, 24x CD), ultraslim, SATA I DVD Super Multi ultra slim , (8x DVD; 24x CD), ultraslim, SATA I
-----------------------	--

Hard disk drives

HDD SATA, 6 Gb/s, 10 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
HDD SATA, 6 Gb/s, 8 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
HDD SATA, 6 Gb/s, 6 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
HDD SATA, 6 Gb/s, 4 TB, 7,200 rpm, 512n, hot-plug, 3.5-inch, business critical
HDD SATA, 6 Gb/s, 2 TB, 7,200 rpm, 512n, hot-plug, 3.5-inch, business critical
HDD SATA, 6 Gb/s, 2 TB, 7,200 rpm, 512n, hot-plug, 2.5-inch, business critical
HDD SATA, 6 Gb/s, 2 TB, 7,200 rpm, 512e, hot-plug, 2.5-inch, business critical
HDD SATA, 6 Gb/s, 1 TB, 7,200 rpm, 512n, hot-plug, 3.5-inch, business critical
HDD SATA, 6 Gb/s, 1 TB, 7,200 rpm, 512n, hot-plug, 2.5-inch, business critical
HDD SATA, 6 Gb/s, 1 TB, 7,200 rpm, 512e, hot-plug, 2.5-inch, business critical

Hard disk drives

HDD SAS, 12 Gb/s, 900 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 900 GB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 600 GB, 15,000 rpm, hot-plug, 3.5-inch, enterprise
HDD SAS, 12 Gb/s, 600 GB, 15,000 rpm, 512n, hot-plug, 2.5-inch, enterprise, SED
HDD SAS, 12 Gb/s, 600 GB, 15,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 600 GB, 10,000 rpm, 512n, hot-plug, 3.5-inch, enterprise
HDD SAS, 12 Gb/s, 600 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 600 GB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 600 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise, SED
HDD SAS, 12 Gb/s, 450 GB, 15,000 rpm, hot-plug, 3.5-inch, enterprise
HDD SAS, 12 Gb/s, 450 GB, 15,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 300 GB, 15,000 rpm, hot-plug, 3.5-inch, enterprise
HDD SAS, 12 Gb/s, 300 GB, 15,000 rpm, 512n, hot-plug, 2.5-inch, enterprise, SED
HDD SAS, 12 Gb/s, 300 GB, 15,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 300 GB, 10,000 rpm, 512n, hot-plug, 3.5-inch, enterprise
HDD SAS, 12 Gb/s, 300 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise, SED
HDD SAS, 12 Gb/s, 300 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 10 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, enterprise, SED
HDD SAS, 12 Gb/s, 10 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
HDD SAS, 12 Gb/s, 8 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
HDD SAS, 12 Gb/s, 6 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, enterprise, SED
HDD SAS, 12 Gb/s, 6 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
HDD SAS, 12 Gb/s, 4 TB, 7,200 rpm, hot-plug, 3.5-inch, business critical
HDD SAS, 12 Gb/s, 4 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
HDD SAS, 12 Gb/s, 2 TB, 7,200 rpm, hot-plug, 3.5-inch, business critical
HDD SAS, 12 Gb/s, 2 TB, 7,200 rpm, 512n, hot-plug, 2.5-inch, business critical
HDD SAS, 12 Gb/s, 2 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
HDD SAS, 12 Gb/s, 2 TB, 7,200 rpm, 512e, hot-plug, 2.5-inch, business critical
HDD SAS, 12 Gb/s, 1.8 TB, 10,000 rpm, 512e, hot-plug, 3.5-inch, enterprise
HDD SAS, 12 Gb/s, 1.8 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise, SED
HDD SAS, 12 Gb/s, 1.8 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 1.2 TB, 10,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 1.2 TB, 10,000 rpm, 512n, hot-plug, 3.5-inch, enterprise
HDD SAS, 12 Gb/s, 1.2 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 1.2 TB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise, SED
HDD SAS, 12 Gb/s, 1 TB, 7,200 rpm, hot-plug, 3.5-inch, business critical
HDD SAS, 12 Gb/s, 1 TB, 7,200 rpm, 512n, hot-plug, 2.5-inch, business critical
HDD SAS, 12 Gb/s, 1 TB, 7,200 rpm, 512e, hot-plug, 2.5-inch, business critical

	SSD M.2 SATA, 6 Gb/s, 150 GB, non hot plug, enterprise, 1.5 DWPD (Drive Writes Per Day for 5 years)
	SSD M.2 SATA, 6 Gb/s, 150 GB, non hot plug, enterprise
SCSI / SAS Controller	LSI PSAS CP400e LP SAS Ctrl. 12 Gbit/s 8 ports ext. PCIe 3.0 x8 Fujitsu PSAS CP400i SAS Ctrl. 12 Gbit/s 8 ports int. PCIe 3.0 x8
RAID Controller	Fujitsu PRAID EP540i LP, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, NVMe-PCIe 8 Gbit/s (coming Q1/2018) 8 Gbit/s 16 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 4 GB, Optional FBU based on LSI SAS3516 Fujitsu PRAID EP420i, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 2 GB, Optional FBU based on LSI SAS3108 Fujitsu PRAID EP420i for SafeStore, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 2 GB, Optional FBU based on LSI SAS3108 Fujitsu PRAID EP400i, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 1 GB, Optional FBU based on LSI SAS3108 Fujitsu PRAID CP400i, RAID Ctrl., SAS/SATA 12 Gbit/s, 8 ports int. RAID level: 0, 1, 1E, 10, 5, 50, No FBU support
Fibre Channel controller	Fibre Channel Host Bus Adapter 1 x 32 Gbit/s Cavium QLE2740 MMF LC-style Fibre Channel Host Bus Adapter 2 x 32 Gbit/s Cavium QLE2742 MMF LC-style Fibre Channel Host Bus Adapter 1 x 32 Gbit/s Emulex LPe32000-M6-F MMF LC-style Fibre Channel Host Bus Adapter 2 x 32 Gbit/s Emulex LPe32002-M6-F MMF LC-style Fibre Channel Host Bus Adapter 1 x 16 Gbit/s Qlogic QLE2690 LC-style Fibre Channel Host Bus Adapter 2 x 16 Gbit/s Qlogic QLE2692 LC-style Fibre Channel Host Bus Adapter 1 x 16 Gbit/s Emulex LPe31000-M6-F MMF LC-style Fibre Channel Host Bus Adapter 2 x 16 Gbit/s Emulex LPe31002-M6-F MMF LC-style
Communication, Network	Converged Network Adapter 2 x 10 Gbit/s PCIe 3.0 x8 SFP+ (Emulex) Ethernet Ctrl. 2 x 10 Gbit/s PCIe 3.0 x8 10Gbit/s Eth (RJ45) (Emulex) Ethernet Ctrl. 2 x 10 Gbit/s PCIe 3.0 x8 RJ45 (Intel®) Ethernet Ctrl. 2 x 10 Gbit/s PCIe 3.0 x8 SFP+ (Emulex) Ethernet Ctrl. 2 x 10 Gbit/s PCIe 3.0 x8 SFP+ (Intel®) Ethernet Ctrl. 2 x 1 Gbit/s PCIe 2.1 x4 RJ45 (Intel®) Ethernet Ctrl. 4 x 10 Gbit/s PCIe 3.0 x8 SFP+ (Intel®) Ethernet Ctrl. 4 x 1 Gbit/s PCIe 2.1 x4 RJ45 (Intel®) InfiniBand HCA 1 x 100 Gbit/s PCIe 3.0 x16 QSFP for the US market max. one IB HCA 100Gb controller can be installed (Mellanox) InfiniBand HCA 1 x 56 Gbit/s PCIe 3.0 x8 QSFP for the US market max. one IB HCA 56Gb controller can be installed (Mellanox) InfiniBand HCA 2 x 100 Gbit/s PCIe 3.0 x16 QSFP for the US market max. one IB HCA 100Gb controller can be installed (Mellanox) InfiniBand HCA 2 x 56 Gbit/s PCIe 3.0 x8 QSFP for the US market max. one IB HCA 56Gb controller can be installed (Mellanox) Interface modul for Dynamic LoM 2 x 10 Gbit/s RJ45 (Intel®) Interface modul for Dynamic LoM 2 x 10 Gbit/s SFP+ (Intel®) Interface modul for Dynamic LoM 4 x 10 Gbit/s SFP+ (Intel®) Interface modul for Dynamic LoM 4 x 1 Gbit/s RJ45 (Intel®) Omni Path 1 x PCIe 3.0 x16 (Intel®)
Rack infrastructure	Rackmount kit full extraction (815mm), tool less mounting, length variable 559-914mm Rackmount kit full extraction (815mm), tool less mounting, length variable 559-914mm Rackmount kit tool less mounting Cable Management 1U for PRIMECENTER- and 3rd-party racks
Warranty	
Warranty period	3 years
Warranty type	Onsite warranty
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty/Index.asp?LNG=COM

Warranty

Product Support Services - the perfect extension

Support Pack Options	Globally available in major business areas: 9x5, Next Business Day Onsite Response Time 9x5, 4h Onsite Response Time 24x7, 4h Onsite Response Time
Recommended Service	24x7, Onsite Response Time: 4h - For locations outside of EMEA please contact your local Fujitsu partner.
Service Lifecycle	5 years after end of product life
Service Weblink	http://www.fujitsu.com/fts/products/product-support-services/

More information

Fujitsu OPTIMIZATION Services

In addition to Fujitsu PRIMERGY RX2530 M4, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Built on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offerings. This allows customers to select from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu PRIMERGY RX2530 M4, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
<http://www.fujitsu.com/primergy>

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
Copyright 2017 FUJITSU LIMITED

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Technology Solutions GmbH

Website: www.fujitsu.com
2017-08-08 INT-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
Copyright 2017 FUJITSU LIMITED